P400E

3-AXIS SLIDING TABLE SAW





FEATURES

- Programmable rip fence with maximum cutting width of 51”
- Programmable blade tilting with automatic cutting height correction and speed display
- Programmable rise/fall of the saw unit
- Motorized scoring axial and height adjustment
- Aluminum extruded crosscut fence with (2) flip stops
- Convenient angle adjustment for mitre cuts
- (3) saw blade speeds for optimum cutting results in various materials
- 7.5 HP main motor with 1HP scoring motor
- Precision anodized aluminum sliding table with prismatic rollers running on precision ground steel guides
- Solid cast iron main table which is ground and polished
- Heavy-duty outrigger for strong support of work-piece during cutting operations
- Overhead CE blade guard with dust port
- Complete with eccentric clamp and wedge for solid wood cutting

SPECIFICATIONS

Cast iron fixed table dimension	27 ½” x 39.4”
Sliding table dimension	126” x 15 ½”
Max. main saw blade diameter	400mm (15.75”)
Main saw bore	30 mm
Max. cutting height w/ blade at 90°	4.13”
Max. cutting height w/ blade at 45°	2 ¾”
Main saw motor	7.5 HP (5.5 Kw)
Main blade speed	3000/ 4000/ 5000 RPM
Scoring saw blade	120 mm (4.72”)
Scoring saw blade bore	20 mm
Scoring blade motor	1 HP (0.75 kw)
Scoring blade speed	8000 RPM
Cutting width	51.2”
Cutting width adjustment	NC control
Blade tilting adjustment	NC control (0°~45°)
Main saw height adjustment	NC control
Scoring saw height adjustment	Motorized
Scoring saw direction adjustment	Motorized
Main blade speed show	Digital
Crosscut fence	Manual (Digital optional)
Dust collection system	4.72” / 2.4” (120/ 60 mm)
Machine total weight	2490 lbs.
Machine shipping weight	2530 lbs.
Sliding table shipping weight	433 lbs.
Electrics	230/3/60 26.2 Full Load Amps (Must be within +/- 5%)

PMB #104 1124 Fir Avenue
Blaine, WA 98230

T: 1.888.982.2683
F: 604.540.1780

Youtube // @CantekMachinery
Twitter // @CantekMachinery

www.cantekamerica.com
sales@cantekamerica.com

P405M

SLIDING TABLE SAW WITH SCORING







FEATURES

- 10’ sliding table with 51” rip capacity
- 7.5 HP main motor with 1HP scoring motor
- Precision anodized aluminum sliding table with prismatic rollers running on precision ground steel guides
- Solid cast iron main table which is ground and polished
- Heavy-duty outrigger for strong support of work-piece during cutting operations
- Solid rip fence with manual fine adjustment and locking lever
- Optional overhead saw blade guard included (CE-type)
- Motorized saw blade rise/fall
- Manual tilting with gravity dial indicator for angle position
- Eccentric hold down clamp included
- Aluminum extruded crosscut fence with two flip stops with dual metric and inch rulers

SPECIFICATIONS

Cast iron fixed table dimension	23.6” x 39.4”
Sliding table dimension	126” x 15.16”
Max. main saw blade diameter	400mm (15.75”)
Main saw bore	30mm
Max. cutting height with blade at 90°	4.14”
Max. cutting height with blade at 45°	2 ¾”
Main motor power	7.5 HP (5.5 Kw)
Main blade speed	3000/ 4000/ 5000 RPM
Scoring saw blade	120 mm (4.72”)
Scoring saw blade bore	20 mm.
Scoring blade motor power	1 HP (0.75 kw)
Scoring blade speed	8000 RPM
Max. ripping width	51.18”
Cutting width adjustment	Manual
Blade tilting adjustment	Manual
Main saw height adjustment	Motorized
Scoring saw height adjustment	Manual
Scoring saw direction adjustment	Manual
Dust collection ports	4 ¾” / 2.4” (120mm / 60mm)
Machine total weight	1900 lbs.
Machine shipping weight	1980 lbs.
Sliding table shipping weight	370 lbs.

PMB #104 1124 Fir Avenue
Blaine, WA 98230

T: 1.888.982.2683
F: 604.540.1780

Youtube // @CantekMachinery
Twitter // @CantekMachinery

www.cantekamerica.com
sales@cantekamerica.com