

CANTEK

HS21T

21-SPINDLE CONSTRUCTION
DRILLING MACHINE



HS21T | 21-SPINDLE CONSTRUCTION DRILLING MACHINE

Flexible boring solution for construction drilling, line drilling, and more.

The Cantek HS21T 21-Spindle Construction Drilling Machine is a versatile construction drilling machine which is capable of line boring, end drilling, & construction drilling functions. The HS21T has a robust fabricated steel construction with precision machined cast iron table. The boring head is cycled pneumatically and runs on precision linear guide rails for smooth drilling cycles. A 2 ½ HP motor powers the boring head with 21 gear driven drill bits and operates at 2800 RPM. Each spindle is equipped with a quick-change chuck to facilitate fast changeovers between drilling operations. The machine comes equipped with fold away side fences which are positioned using a linear scale. The 118" (3 meter) back fence is equipped with (4) flip tops which is ideal for positioning panels during line boring applications and more. The boring head is effortlessly tilted from 0-90° by a pneumatic cylinder. It can also be locked in any position between 0° and 90° for angle drilling operations. Boring depth is quickly and precisely adjusted using a 6-position turret system. Workpieces are held firmly in place by (2) pneumatic clamps.




Centralized control panel



Foot pedal executes boring cycle



21 spindles with quick change chucks for fast boring pattern changeover



Rotary turret system for quick depth setting



Side fences can be safely and easily folded away when not in use



Boring height is conveniently and accurately adjusted with a mechanical counter



Fence can be attached to side fence for boring shelf holes and more



Boring head can be tilted from 0 - 90°

Key Advantages.

- Single line boring machine with 21 spindles (11 RH & 10 LH) at 32mm centers
- Tilttable boring unit can be changed from horizontal to vertical drilling by pneumatic setting
- Pneumatic drilling cycle by convenient foot pedal
- Quick 6-position boring depth selector for fast changeover
- 21 quick change chuck for fast changeover
- Boring unit can be tilted manually for angular drilling
- Adjustable drill feed speed
- Mechanical digital readouts are provided for precise setting of the boring head
- Two-fold away side fences for end boring or drilling smaller components
- Side fences provides convenient positioning of the workpiece using a linear scale for positioning
- 3-meter back fence with 4 adjustable stops for line boring or they can be set on the side fence for dowel drilling on the face of the gable

Specifications.

Distance between center	32mm
Number of spindles	21
Max. drilling depth	3"
Boring head adjustment	0°~90°
Table size	34.33" x 19.3"
Spindle speed	2800 RPM
Motor	2.5HP
Electrics	230/3/60 = 9 Full Load Amps 230/1/60 = 16.9 Full Load Amps
Machine weight	770 lbs
Machine dimensions	38.11"x32 ¼"x 48"