

CANTEK

MX550AU

PORTABLE EDGE BANDER PACKAGE



MX550AU | PORTABLE EDGE BANDER PACKAGE

Take your edgeworker to the job site and edgeband straight or curve parts.

The Cantek MX550AU Portable Edgebander Package is a versatile portable edgebanding solution for the hobbyist or industrial user. It is capable of edgebanding radius or straight workpieces and can be operated as a handheld unit (standard) or a stationary system with the optional table accessory. The edgebander is equipped with a glue pot which uses granulated hot melt glue with an operating temperature range from 120°C to 200°C (250°F to 390°F). The full kit includes the portable edgebander, power trimmer, workpiece clamp set, and dual end cutter. The package also comes with packaging for each item and a dolly to make it extra easy to take with you to the site.

Package includes:



Trolley



MX550
Portable edgebander



Glue



PD80
Portable trimmer



TK65
Dual end trimmer



VH03N
Workpiece clamping kit



Optional:
BC23 Mobile dispenser



Optional:
ST95B Stationary worktable set



Optional:
ST97 Guide component kit for
straight edges on the ST95B

Key Advantages.

- Can apply edgebanding material from 0.4~3mm thick
- Straightforward operation with ergonomic handles and material support plate
- Simple maintenance
- Edgebands straight as well as curved surfaces
- Light weight & portable unit which can be taken to the jobsite
- Automatic glue application with adjustable glue amount control
- Works on 75-90° surfaces
- Glue pot with quick heating time of approximately 8 minutes
- Variable feed speed from 6.5~20 FPM (2-6 m/min)

Simple Operation.

Straightline and Contour Edgebanding

Our portable edgebanders are perfect for all varieties and shapes of workpieces. For contoured or curved surfaces, the minimum interior radius is 25mm (1").

Hotmelt Glue for Edgebanding Bond

The glue is applied directly onto the edgebanding or edging tape. Maintain steady pressure on the workpiece against the feeding roller to apply the edgebanding or edging tape at desired temperature.

Glue-Free Edgebanding

Save money on your edgebanding as the MX550 uses standard tape and does not require pre-glue edgebanding.

Material Compatibility

The MX550 can work with PVC, melamine, laminate, wood and metal edgebanding and edge tape of 0.3mm – 3mm thickness and 10mm – 65mm width.

Angle Adjustment

Our edgebanders can operate on tilted surfaces of 75°-90°, making beveled surfaces as simple as straight ones.

Quick to Start

The MX550 edgebander requires approximately 8 minutes to obtain operating temperature with a full pot of glue. Heat up time is reduced with less glue in the pot.

Built to Last

Quality construction and rigorous testing ensure the MX550 will perform time after time.

Portable and Stationary Use

Designed for transportation and space-efficiency, our MX550 comes with a durable and lightweight case. For handheld operation, workpieces can be secured with our VH03N Vacuum Clamp Set. For stationary operation, the MX550 can also be secured to our optional ST95B Stationary Worktable depending on your needs.

Specifications.

Tape thickness	0.4 ~ 3mm (0.0016~0.118")
Width of tape	10 ~ 65mm (0.4~2.55")
Feeding speed	2 ~ 6 m/min (6.5~20 FPM)
Output power	1.15 HP (855 W) 115/1/60
Glue pot temperature	120°C~200°C (250°F~390°F)
Glue pot capacity	400 ml (13.5 oz)
Unit weight	8.7 kgs (19 lbs)